

## SAFETY CAGE TYPE SIKO



Type SIKO/L

Type SIKO

Type	Dimensions	Floor area in mm	Total permitted weight in kg	Weight in kg	Fork sleeve inside dimensions in mm		
	in mm (l x w x h)				A	B	C
SIKO	1115 x 1200 x 1890	800 x 1200	300	90	600	200	80
SIKO/L	1290 x 800 x 1890	1200 x 800	300	96	160	200	80

### Safety for repairs and maintenance



- sturdy construction made of round pipes
- nonslip access safety platform
- number of persons permitted: 2
- through fork sleeves with safety mechanism to prevent slipping
- underrun protection device ensures pick-up via fork sleeves
- with galvanized tool deposit
- approved by the german technical inspection agency "TÜV", in compliance with the "BGV" (German accident prevention regulations)

### Types available

#### Type SIKO

- picked up lengthwise by a forklift truck


#### Type SIKO/L

- picked up crosswise by a forklift truck

### Accessory

- 2 swivel + 2 fixed polyamide castors  
Ø 180 mm, one swivel castor with brake  
- construction height 220 mm

Fork sleeve inside dimensions in mm



## SAFETY CAGE TYPE SIKO-M



Type	Dimensions	Floor area in mm	Total permitted weight in kg	Weight in kg	Fork sleeve inside dimensions in mm		
	in mm (l x w x h)				A	B	C
SIKO-M	1040 x 835 x 1895	740 x 740	240	54	280	200	80

Finish:

RAL 2000

### The economic alternative



- sturdy construction made of round pipes
- nonslip access safety platform
- number of persons permitted: 2
- fork sleeves with safety mechanism to prevent slipping
- with galvanized tool deposit
- approved by the german technical inspection agency "TÜV", in compliance with the "BGV" (German accident prevention regulations)

Fork sleeve inside dimensions in mm

